



EUROPEAN COMMISSION  
DIRECTORATE-GENERAL  
TAXATION AND CUSTOMS UNION  
Digital Delivery of Customs and Taxation Policies  
**Customs Systems**

# Operational FAQ

## ICS2

Date:	20/05/2022
Status:	Submitted for acceptance (SfA)
Version:	2.30 EN
Author:	ITSM3-TES
Approved by:	DG TAXUD
Reference number:	DLV.3.2.3.7
Public:	DG TAXUD internal
Confidentiality:	Publicly available (PA)

## Document control information

Property	Value
<b>Title</b>	Operational FAQ
<b>Subtitle</b>	ICS2
<b>Author</b>	ITSM3-TES
<b>Project owner</b>	Head of Unit of DG TAXUD Unit B3
<b>Solution provider</b>	DG TAXUD Unit B3 Customs Systems
<b>DG TAXUD Project Manager</b>	Bartlomiej Bzdela
<b>Version</b>	2.30 EN
<b>Confidentiality</b>	Publicly available (PA)
<b>Date</b>	20/05/2022

## Contract information

Property	Value
<b>Framework Contract</b>	TAXUD/2017/CC/138
<b>Specific Contract</b>	SC09

## Document history

The document author is authorised to make the following types of changes to the document without requiring that the document be re-approved:

- Editorial, formatting, and spelling;
- Clarification.

To request a change to this document, contact the document author or project owner.

Changes to this document are summarised in the table in reverse chronological order (latest version first).

Version	Date	Description	Action <sup>1</sup>	Section
2.30	20/05/2022	Document re-submitted for acceptance (re-SfA)	I/R	All
2.20	19/05/2022	Document submitted for acceptance (SfA).	I/R	All
2.10	04/05/2022	Document submitted for review (SfR). Document updated to accommodate Questions and Answers in scope of ICS2 operations and Conformance Testing irrespective of a specific ICS2 Release.	I/R	Added sections: 2.2.10, 2.2.11, 2.2.12, 2.2.13, 2.3.6, 2.3.7, 2.3.8, 3.1.2, 3.1.3, 3.2.1, 3.2.2, 3.2.3, 3.2.5, 3.2.14 Modified Sections: 1.1, 1.2, 1.3, 1.4, 1.5, 2.2.2, 2.2.3, 3.2.6, 3.2.7, 3.2.10, 3.2.16, 3.2.19, 3.2.22
2.00	11/03/2022	Document submitted for acceptance (SfA).	I/R	All
1.90	03/03/2022	Document submitted for review (SfR).	I/R	Modified sections 2.3.5, 3.2.20
1.80	13/01/2022	Document submitted for acceptance (SfA).	I/R	All
1.70	05/01/2022	Document submitted for review (SfR).	I/R	Added section 3.2.18, 3.2.19, 3.2.20
1.60	15/11/2021	Document submitted for acceptance (SfA).	I/R	All
1.50	05/11/2021	Document submitted for review (SfR).	I/R	Added section 2.3.5
1.40	13/09/2021	Document submitted for acceptance (SfA).	I/R	All
1.30	03/09/2021	Document submitted for review (SfR) upon bi-monthly update.	I/R	Added sections 2.3.4, 3.2.15, 3.2.16, 3.2.17

Version	Date	Description	Action <sup>1</sup>	Section
1.20	13/07/2021	Document submitted for acceptance (SfA).	I/R	All
1.10	05/07/2021	Document submitted for review (SfR) upon bi-monthly update.	I/R	Added sections 2.1.9, 2.2.9, 3 Modified sections 1.1, 1.3
1.00	17/05/2021	Document submitted for acceptance (SfA).	I/R	All
0.10	05/05/2021	Document submitted for review (SfR).	I/R	All
0.01	01/04/2021	Initial draft	I/R	All

<sup>1</sup> Action: I=Insert R=Replace

## Configuration management: document location

No previously accepted version of this document exists.

# Table of contents

<b>1</b>	<b>INTRODUCTION.....</b>	<b>8</b>
1.1	Document purpose.....	8
1.2	Target audience .....	8
1.3	Scope .....	8
1.4	Structure .....	8
1.5	Reference documents .....	8
1.6	Applicable documents .....	9
1.7	Abbreviations & acronyms.....	9
1.8	Definitions.....	11
<b>2</b>	<b>OPERATIONAL FREQUENTLY ASKED QUESTIONS (FAQ).....</b>	<b>12</b>
2.1	FAQ related to Central side.....	12
2.1.1	What are the URLs for ICS2 CR User Interface?.....	12
2.1.2	What are the URLs for ICS2 Monitoring & Business Statistics tool?.....	12
2.1.3	In case of question regarding the value of a timer in production, what is the proper communication channel for this to be addressed? .....	12
2.1.4	What process should be followed in order for an MS to enter ICS2 Operations? .....	12
2.1.5	Who is responsible for the registration of the national web services in the CCN2ng platform? .....	12
2.1.6	Which are the physical addresses of the NES partner endpoints that should be registered in the CCN2ng platform? .....	12
2.1.7	Which data elements should be used in XI and in GB?.....	13
2.1.8	Which country codes can be used under the code list CL718?.....	13
2.2	FAQ related to MS .....	13
2.2.1	How an MS user can access ICS2 Monitoring & Business Statistics tool?.....	13
2.2.2	How may an MS register a planned unavailability? .....	13
2.2.3	How may an MS register an unplanned unavailability? .....	14
2.2.4	What is the required role in order for a user to register a new unavailability? .....	14
2.2.5	Which time zone shall MSs use to declare their unavailability in ICS2 Monitoring & Business Statistics tool? .....	14
2.2.6	How may a user download a message from the ICS2 Monitoring & Business Statistics tool?.....	14
2.2.7	What a MS should take into consideration regarding S2S user for NES in CCN2ng Oracle Identity Management? .....	14
2.2.8	What elements a MS should modify for the preparation of WSDL files to be uploaded on CCN2ng Platform in production environment?.....	14
2.2.9	Are there specific message types (IExxxx) where large messages from CR can be expected?.....	15
2.2.10	What are the technical differences between the .xml versions of the messages for Release 1 & Release 2?.....	15
2.2.11	In Release 2, in the messages sent from CR (such as IE4R02/IE4R03), is the hyperlink field URI a link to an external website or to a physical attachment located within the ICS2 CR?.....	16
2.2.12	Which roles does the user need to have in order to download the attachment from CR UI? 16	
2.2.13	In ICS2 Release 2 a new 'URI' field has been added. The filename field is still mandatory. For an attachment this would be the file name, for a URI, would this be the file path? .....	16
2.3	FAQ related to EO.....	17

2.3.1	What does mean the condition Cxxx for the optionality of data element 'Commodity code' in an IE3F32 message?.....	17
2.3.2	What is the process in case an EO would like to add further good items within an existing ENS filling?.....	17
2.3.3	In case an EO (sender) asks for a message with specific LRN, what is the process for detecting such message at central side?.....	17
2.3.4	How the phone numbers which are included in the ENS Filings (sent by the EOs) are validated from STI? Please also include some examples. ....	17
2.3.5	Is there any alert which is triggered before the expiration of the registered certificates in the UUM&DS system?.....	18
2.3.6	Will there be the possibility for EOs with few movements to lodge their ENS via a GUI, as it will not be feasible for these EOs to develop a full-fledged ICS2 system-to-system application? .....	18
2.3.7	Is there anything an Airline Company has to do in order to announce an ITSP being the technical connection? .....	18
2.3.8	What should be the business content of messages if the user of the services of an ITSP is a GHA (Ground Handling Agent) that represents multiple Airline Companies? .....	18
<b>3</b>	<b>CONFORMANCE TESTING FREQUENTLY ASKED QUESTIONS (FAQ) .....</b>	<b>19</b>
3.1	FAQ related to MS .....	19
3.1.1	What is the use of Synergia and how to obtain a Synergia account?.....	19
3.1.2	What is the usage of MON&BS as supportive tool to the EO-Self Conformance Campaign? .....	19
3.1.3	Who is involved in the IsAlive (connectivity verification)?.....	19
3.2	FAQ related to EO.....	20
3.2.1	Which documents should an EO or ITSP Provider consult for their preparation prior to conformance testing?.....	20
3.2.2	Which is the URL for ICS2 STI-STP User Interface?.....	20
3.2.3	Which steps should be followed by an Economic Operator (or an ITSP) in order to establish the AS4 connectivity prior to the conformance testing?.....	20
3.2.4	How many certificates should be used by the EOs? .....	21
3.2.5	From which Certificate Authorities (CAs) an EO can issue its certificate for ICS2 message sealing (signing)? .....	21
3.2.6	Who is responsible for managing the National UUM&DS alternate list? .....	22
3.2.7	Who is responsible for managing the LOTL? .....	22
3.2.8	How does an EO communicate its sealing certificate?.....	22
3.2.9	How to verify the successful registration of EO System digital certificate? .....	22
3.2.10	Can an EO register the same sealing certificate in CONF and PROD?.....	22
3.2.11	What is usage of sealing certificate in AS4 message exchanges with ICS2? .....	22
3.2.12	How to register a sealing certificate depending if you are or not the holder of the key?.....	22
3.2.13	How to use UUM&DS system?.....	23
3.2.14	Which UUM&DS Business Profiles should an EO have in the scope of Self-Conformance Test Campaign? .....	23
3.2.15	Which EORI number should an EO use? .....	24
3.2.16	How should an EO configure P-Mode?.....	24
3.2.17	In the response messages an EO receives from TAPAS, what is a globally unique identifier for a specific multipart/related MIME part? .....	24
3.2.18	What should be the "MPC" use attribute in an incoming user message? .....	24
3.2.19	Which are the most common issues identified during the ICS2 connectivity setup trials with EOs/ITSPs? .....	24
3.2.20	Which elements should contain unique values in the ENS fillings?.....	24

3.2.21	What is the meaning of the N99 error codes?.....	25
3.2.22	Which is the correct expression for the time values inside fillings?.....	25
3.2.23	How should an EO raise an issue to Service Desk? .....	25

List of tables

Table 1: Reference documents ..... 9

Table 2: Applicable documents..... 9

Table 3: Abbreviations and acronyms..... 11

Table 4: Definitions ..... 11

List of figures

No table of figures entries found.

# 1 INTRODUCTION

## 1.1 DOCUMENT PURPOSE

This document incorporates the most common questions raised by MSs and EOs as well as the clarifications that have been provided by DG TAXUD and contractors of DG TAXUD who are involved in the support and monitoring activities of ICS2 operations and conformance testing. Moreover, this document incorporates questions about how to handle different types of incidents which have been detected during production of ICS2.

## 1.2 TARGET AUDIENCE

The target audience for this document includes any person from the National Administrations and the Economic Operators who are involved in the ICS2.

## 1.3 SCOPE

The scope of this document is to consolidate the knowledge from the most common questions raised by MSs and EOs as well as the clarifications that have been provided by DG TAXUD and contractors of DG TAXUD who are involved in the support and monitoring activities of ICS2 operations.

## 1.4 STRUCTURE

This document is organised as follows:

- **Chapter 1 – Introduction:** describes the scope and the objectives of the document;
- **Chapter 2 – Operational Frequently Asked Questions (FAQ):** enlists the questions most frequently raised by DG TAXUD, contractors of DG TAXUD, MSs and EOs, along with the respective answers in relation to ICS2 Operational topics;
- **Chapter 3 – Conformance Testing Frequently Asked Questions (FAQ):** enlists the questions most frequently raised by DG TAXUD, contractors of DG TAXUD, MSs and EOs, along with the respective answers in relation to Conformance Testing topics.

## 1.5 REFERENCE DOCUMENTS

The table below lists the documents that are referred to in the current document.

Ref.	Title	Originator	Version	Date
R01	<a href="#">ICS2 Design Document for National Applications</a>	CUST-DEV3	4.20	01/03/2022
R02	<a href="#">MS Conformance Test Case Specifications Release 1</a>	CUST-DEV3	3.40	05/03/2021
R03	<a href="#">EO Conformance Test Case Specifications Release 1</a>	CUST-DEV3	2.40	05/03/2021
R04	<a href="#">EO Conformance Test Scenarios Specifications Release 1</a>	CUST-DEV3	1.70	23/12/2020
R05	<a href="#">EO Conformance Test Organisation Document (CTOD) for Release 1</a>	ITSM3-TES	1.23	07/04/2021
R06	<a href="#">ICS2 HTI Interface Control Document</a>	CUST-DEV3	3.30	02/03/2022
R07	<a href="#">MS Conformance Test Organisation Document (CTOD) for Release 1</a>	ITSM3-TES	1.80	15/06/2021



Ref.	Title	Originator	Version	Date
R08	<a href="#">ICS2 Rules and Conditions</a>	DG TAXUD ICS2 Project Team	1.24	19/03/2021
R09	<a href="#">MS Business Continuity Plan</a>	DG TAXUD ICS2 Project Team	1.24	04/04/2022
R10	<a href="#">Test Design Specifications for Member States Conformance Test Scenarios for Release 2</a>	SOFT-DEV	1.91	03/02/2022
R10	<a href="#">ICS2 Monitoring - Use Case Specifications</a>	CUST-DEV3	5.30	01/04/2022
R12	<a href="#">CCN2-CFSS-R1.5 System Functional Specifications</a>	CCN2-DEV	14.00	18/01/2022
R13	<a href="#">MS-TDS-Conformance Test Cases for Release 2</a>	SOFT-DEV	1.70	10/03/2022
R14	<a href="#">ICS2 EOs Common Technical System Specifications package for ICS2 Release 2</a>	DG TAXUD	N/A	15/02/2022
R15	<a href="#">Conformance Test Organisation Document (CTOD) for EO for Release 2</a>	ITSM3-TES	1.20	10/02/2022
R16	<a href="#">Test Design Specifications for Economic Operator Conformance Test Scenarios for Release 2</a>	SOFT-DEV	1.80	20/01/2022
R17	<a href="#">Test Design Specifications for Economic Operator Conformance Test Cases for Release 2</a>	SOFT-DEV	1.40	18/02/2022
R18	<a href="#">Conformance Test Organisation Document (CTOD) for MS for Release 2</a>	ITSM3-TES	1.20	02/02/2022

**Table 1: Reference documents**

## 1.6 APPLICABLE DOCUMENTS

The table below lists the documents to which the current document must be compliant.

Ref.	Title	Originator	Version	Date
A01	TEMPO – Glossary of Terms	DG TAXUD	2.01-EN	07/04/2006
A02	Specific Contract 09	DG TAXUD	N/A	01/06/2021
A03	Framework Contract	DG TAXUD	N/A	26/09/2016

**Table 2: Applicable documents**

## 1.7 ABBREVIATIONS & ACRONYMS

For a better understanding of the present document, the following table provides a list of the principal abbreviations and acronyms used.

See also the ‘list of acronyms’ on TEMPO.

Abbreviation/Acronym	Definition
AS4	Applicability Statement 4
CA	Certificate Authority
CCN2ng	Common Communication Network 2 next generation
CEF	Connecting Europe Facility
CET	Central European Time
CL	Code List
CoA	Confirmation of Arrival
CoD	Confirm on Delivery

Abbreviation/Acronym	Definition
CoE	Confirmation of Exception
CR	Common Repository
CSD	Central Service Desk
CS/RD2	Common Service for Reference Data version 2
CT	Conformance Testing
CTC	Conformance Test Cases
DG TAXUD	Directorate General - Taxation and Customs Union
E2E	End-to-End
EIDAS	Electronic Identification, Authentication and trust Services
ENS	Entry Summary Declaration
EO	Economic Operator
EORI	Economic Operators Registration and Identification number
ESS	Employee Self Service (part of SYNERGIA SMT) ( <a href="https://itsmtaxud.europa.eu/smt/ess.do">https://itsmtaxud.europa.eu/smt/ess.do</a> )
FAQ	Frequently Asked Questions
GB	Great Britain
GMT	Greenwich Mean Time Zone
HTI	Harmonised Trader Interface
ICD	Interface Control Document
ICS2	Import Control System 2
ID	Identity Document
ITSM	IT Service Management
ITSP	IT Service Provider
LOTL	EU List of eIDAS Trusted Lists
LRN	Local Reference Number
MIME	Multipurpose Internet Mail Extensions
MPC	Message Partition Channels
MON	ICS2 Monitoring and Business Statistics Tool
MS	Member State
NES	National Entry System
NSD	National Service Desk
NPTL	National Project Team Leader
OIM	Oracle Identity Management
OMS	Other Member State
OPS	Operations
STI	Shared Trader Interface
STP	Specific Trader Portal
TAPAS	DG TAXUD Access Point for AS4 System
TES	Trans-European Systems
TI or ICS2 TI	ICS2 Trader Interface
UI	User Interface
UTC	Coordinated Universal Time
UUM&DS	Unified User Management and Digital Signatures
XI	United Kingdom (Northern Ireland)

Abbreviation/Acronym	Definition
WAYF	Where Are You From
WSDL	Web Services Description Language

**Table 3: Abbreviations and acronyms**

## 1.8 DEFINITIONS

For a better understanding of the present document, the following table provides a list of the principal terms used.

See also the ‘glossary’ on TEMPO.

Term	Definition
AS4	AS4 (Applicability Statement 4) is a Conformance Profile of the OASIS ebMS 3.0 specification and represents an open standard for the secure and payload-agnostic exchange of business-to-business documents using web services.
AS4 access point	An AS4 access point is an operational IT component that implements the AS4 specifications for the exchange of information with other AS4 access points, be it a Trader Interface (STI/NTI) or an access point used by an Economic Operator (EO).
Certificate Authority	A Certificate Authority (CA) is an entity that issues digital certificates. A digital certificate certifies the ownership of a public key by the named subject of the certificate. This allows others (relying parties) to rely upon signatures or on assertions made about the private key that corresponds to the certified public key. A CA acts as a trusted third party—trusted both by the subject (owner) of the certificate and by the party relying upon the certificate. The format of these certificates is specified by the X.509 standard.
Conformance Testing	This testing is done to obtain technical assurance that a National Administration or an Economic Operator is ready to enter the Trans-European System without risk of disturbing the parties already in operation in the system.
Electronic Certificate	An electronic or digital certificate is an attachment to an electronic message used for security purposes. The most common use of a digital certificate is to verify that a user sending a message is who he or she claims to be, and to provide the receiver with the means to encode a reply. An individual wishing to send an encrypted message applies for a digital certificate from a Certificate Authority (CA). The CA issues an encrypted digital certificate containing the applicant's public key and a variety of other identification information. The CA makes its own public key readily available through print publicity or perhaps on the Internet.
Electronic seal	According to the eIDAS regulation, an electronic seal is a piece of data attached to an electronic document or other data, which ensures data origin and integrity. Technically similar to digital signatures, electronic seals serve as evidence that an electronic document was issued by a specific legal entity, not a natural person.
ITSM Contractor	DG TAXUD contractor (ITSM3-OPS, ITSM3-TES) responsible for operating the central services and testing the centrally developed applications.

**Table 4: Definitions**

## 2 OPERATIONAL FREQUENTLY ASKED QUESTIONS (FAQ)

### 2.1 FAQ RELATED TO CENTRAL SIDE

#### 2.1.1 What are the URLs for ICS2 CR User Interface?

Conformance: <https://u2s.conf.ccn2.taxud/ics2-cr-web-ccn2/index.jsp>

Production: <https://u2s.prod.ccn2.taxud/ics2-cr-web-ccn2/index.jsp>

#### 2.1.2 What are the URLs for ICS2 Monitoring & Business Statistics tool?

Conformance: <https://u2s.conf.ccn2.taxud/ics2-mon/index.html>

Production: <https://u2s.prod.ccn2.taxud/ics2-mon/index.html>

#### 2.1.3 In case of question regarding the value of a timer in production, what is the proper communication channel for this to be addressed?

An MS must address any request around value of timer in production directly to DG TAXUD via secure email. It is highlighted that such information must not be shared with EO.

#### 2.1.4 What process should be followed in order for an MS to enter ICS2 Operations?

After the successful completion of the CT activities, a ticket should be registered in order the CL717 filter to be updated in CS/RD2 PROD. The CL717 - Country code (ICS2 MS) must include the country code of the MS who is going to enter ICS2 operations. Afterwards, a change should be implemented by ITSM3-OPS in order for the country code to be added from CS/RD2 in ICS2 Coherence Cache Memory in PROD. Above actions have to be done at least one day before the planned GO live date for the NA.

#### 2.1.5 Who is responsible for the registration of the national web services in the CCN2ng platform?

ITSM3-OPS is responsible to register the WSDL files for the national web services in the CCN2ng platform. However, the corresponding WSDL files have to be submitted to ITSM3-OPS by the respective MS. This is done by opening a Service request with CSD to SYNERGIA.

#### 2.1.6 Which are the physical addresses of the NES partner endpoints that should be registered in the CCN2ng platform?

As per section 8.1 from the ICS2 Design Document [R01], the physical addresses of the NES partner endpoints to be registered in the CCN2ng platform should respect the following format:

**`https://{host_IP}:{port}/{serviceURL}`**

and should be supplied by each MS within separate WSDL file per NES service.

The “**`https://{host_IP}:{port}`**” will be common among one NES’s endpoints, allowing the Central CCN2 Team to establish the connectivity between the CCN2ng platform and this NES.

However, an individual endpoint with unique “**`serviceURL`**” will be defined for each NES service:

- CCN2.Service.Customs.EU.ICS.NESControlBAS;
- CCN2.Service.Customs.EU.ICS.NESErrorNotificationBAS;
- CCN2.Service.Customs.EU.ICS.NESNotificationBAS;

- CCN2.Service.Customs.EU.ICS.NESReferralBAS;
- CCN2.Service.Customs.EU.ICS.NESRiskAnalysisBAS.

It is worth to clarify that although each web service holds its own physical address within the same NES, the Destination ID of the NES itself remains the same among all WSDL files and should respect the following naming convention:

**CCN2.Partner.{Country Code}.Customs.TAXUD/ICS\_NES.{ENV}**

where the **{Country Code}** placeholder is the country code of the NES's country (i.e. two-letter country codes with capital letters as per ISO 3166-1 alpha-2) and the **{ENV}** placeholder depends on the environment with possible values:

- CONF: for the Conformance Testing environment;
- PROD: for the Production environment.

For example, the Destination ID of the Austrian (AT) NES in CONF environment is the “CCN2.Partner.AT.Customs.TAXUD/ICS\_NES.CONF”.

### 2.1.7 Which data elements should be used in XI and in GB?

The country code XI (Northern Ireland) is only to be used for the Addressed MS data element. In all other instances, GB should be used for any address or location referred to the United Kingdom, regardless whether it refers to Northern Ireland or any other location in the UK. Even if the XI code is not used, in case of GB code, the ICS2 checks the postal codes and for those that Northern Ireland post code is detected, XI is identified as IMS. According to CLs that are used for each data element, in case of CL717 - Country code (ICS2 MS) applies, XI is used and in case of CL718 - Country code (ISO 3166) applies, GB is used.

### 2.1.8 Which country codes can be used under the code list CL718?

According to ICS2 DG TAXUD, the Country codes used in ICS2 are defined in ISO-3166 and COMMISSION IMPLEMENTING REGULATION (EU) 2020/1470. Country codes that are not subject of those two sources, cannot be added in CL718.

## 2.2 FAQ RELATED TO MS

### 2.2.1 How an MS user can access ICS2 Monitoring & Business Statistics tool?

In order to grant access in ICS2 Monitoring and Business statistics tool, there are required CCN2 roles that needs to be assigned to the users by National CCN2ng User Administrator.

More details about the CCN2 roles as well as general information regarding the ICS2 Monitoring & Business Statistics tool can be found under the following PICS URL:

<https://webgate.ec.europa.eu/pics/group/20607/news/35502>.

### 2.2.2 How may an MS register a planned unavailability?

As per section 3.10 of the Business Continuity Plan document [R09], also published on PICS:

<https://webgate.ec.europa.eu/pics/filedepot/20607?fid=80683>

MS shall use the ICS2 Business Statistics & Monitoring tool (<https://u2s.prod.ccn2.taxud/ics2-mon/index.html>) to register and notify each other about their planned unavailability.

### 2.2.3 How may an MS register an unplanned unavailability?

As per section 3.5 of the Business Continuity Plan document [R09], the NSD of the impacted MS records the unavailability in ICS2 Business Statistics & Monitoring tool: <https://u2s.prod.ccn2.taxud/ics2-mon/screen/unavailability>.

### 2.2.4 What is the required role in order for a user to register a new unavailability?

The required user role is the CCN2 role "Member State Service Support – Availability Manager". With this user role, a national CCN2 user can register unavailability.

### 2.2.5 Which time zone shall MSs use to declare their unavailability in ICS2 Monitoring & Business Statistics tool?

MS users shall register their planned unavailability in their local time zone. The MON & BS UI expects the date time of the planned unavailability always in the local time of the user. The notification e-mail that will follow the registration of the unavailability will convert the local time of the user into CET.

### 2.2.6 How may a user download a message from the ICS2 Monitoring & Business Statistics tool?

With the "Member State Service Support – Messages Operator" role a user should access ICS2 Monitoring & Business Statistics tool. The user should access the webpage dedicated to the search of messages and enter the intended search criteria. The list of retrieved messages is displayed and the user can click on the message (text with blue characters) that would like to export. Then, a pop-up window will appear with more details about this specific message. At the bottom of this pop-up window, user may find an "Export" button. By clicking on this "Export" button, the related message will start to be downloaded.

### 2.2.7 What a MS should take into consideration regarding S2S user for NES in CCN2ng Oracle Identity Management?

While creating the S2S user for NES in the CCN2ng Oracle Identity Management (OIM) in production environment, the "User Login" and the "Common Name" fields should be identical and should be composed either of capital letters only or lower letters only, without any space character (e.g. "xxx.yyy" or "XXX.YYY", but not something like "xXx YyY").

### 2.2.8 What elements a MS should modify for the preparation of WSDL files to be uploaded on CCN2ng Platform in production environment?

In general, it is suggested to use the same WSDL files that were submitted in the scope of the conformance testing, however, MS should consider modifying the following elements:

- The name of the WSDL files should contain the term "PROD" instead of "CONF". For example, the NES Control BAS WSDL file should be named after:  
**CCN2.Service.Customs.EU.ICS.NESControlBAS\_1.0.0\_CCN2.Partner.CC.Customs.TAXUD.ICS\_NES.PROD\_1.0.0.wsdl**
- The address parameter should be updated with the details where NES and acknowledgement services will be exposed in the production environment, according to the below format:

**http(s)://{Partner\_Service\_Host\_IP}:{Partner\_Service\_Port}/{Partner\_Service\_url}**

- The term “CONF” should be replaced by “PROD” in the Destination\_ID parameter:

```
<wsa:Metadata>
  <ccn2:ServiceID>CCN2.Service.Customs.EU.ICS.NESControlBAS</ccn2:ServiceID>
  <ccn2:ServiceName>CCN2      Service      Customs      EU      ICS
  NESControlBAS</ccn2:ServiceName>
  <ccn2:ServiceDescription>CCN2      Service      Customs      EU      ICS
  NESControlBAS</ccn2:ServiceDescription>
  <ccn2:ServiceVersion>1.0</ccn2:ServiceVersion>
  <ccn2:DestinationID>CCN2.Partner.{Country
  Code}.Customs.TAXUD/ICS_NES.PROD</ccn2:DestinationID>
  <ccn2:XMLValidation>false</ccn2:XMLValidation>
</wsa:Metadata>
```

- In case that MS will be using "https" communication, before the upload of the WSDL files, it is required to provide a certificate (signed by your internal or external Certificate Authority) for MS ICS2 application. In this certificate, the Subject Alternative Name (SAN) should contain the Mapped IP (MIP) address. The MIP will be communicated by the Central Network Team to MS through the related ticket and afterwards NA should share the certificate. The WSDL files will be uploaded only after the connectivity is set in place and the certificate is received from the MS.

### 2.2.9 Are there specific message types (IExxxx) where large messages from CR can be expected?

According to CCN2 Functional System Specifications [R12] the maximum size of a message that is sent through CCN2ng is 20MB. If a message exceeds this size, CCN2 will return an error message of type CCN2-VAL-1005. As observed in the message exchange process, the average byte size of the IE4Q02, IE4Q01 and IE4N05 messages is 20KB or less except of the IE4R02 message. As a general rule, a NES should be able to receive messages up to the defined maximum size of 20MB, since this is the specified size limit. Additional information on the physical attachment, which is stored in CR, is provided in [2.2.11](#).

### 2.2.10 What are the technical differences between the .xml versions of the messages for Release 1 & Release 2?

Release 1 and Release 2 messages are distinguished based on XML namespaces and WSDL end-points.

- For Release 1:

The business payload (e.g. IE3F32, ...) is in the xml namespace "urn:wco:datamodel:WCO:CIS:1".

The EO will set the eb:AgreementRef at AS4 level to “EU-ICS2-TI-V1.0”.

The webservice end points for the interactions between CR-NES all refer to ‘V1’ versions (e.g. xmlns=http://xmlns.ec.eu/BusinessActivityService/ICS/IRiskAnalysisOrchestratio...V1).

- For Release 2:

The business payload (e.g. IE3F32, ...) is in the xml namespace " urn:wco:datamodel:eu:ics2:2".

The EO will set the eb:AgreementRef at AS4 level to “EU-ICS2-TI-V2.0”.

The webservice end points for the interactions between CR-NES all refer to ‘V2’ versions (e.g. xmlns=http://xmlns.ec.eu/BusinessActivityService/ICS/IRiskAnalysisOrchestratio...V2).



The R1 and R2 flows are totally separated, both from a content perspective (business payload in different namespace) as well from a technical end-point perspective. R1 and R2 have different WSDL endpoints.

### **2.2.11 In Release 2, in the messages sent from CR (such as IE4R02/IE4R03), is the hyperlink field URI a link to an external website or to a physical attachment located within the ICS2 CR?**

The URI is a link to a CR UI page. The received physical attachment is stored within the CR database, and when the MS recipient wants to retrieve it via a URI, then the CR system generates a URI and populates it in the outgoing message.

The URI generated by the CR system has the following indicative format: “/screen/ensdata/binaryattachment?uuid={UUID}”.

The member state is responsible to add the CR UI context path. With a final result like: “https://ics2domain/ics2-cr-web-ccn2/#/screen/binaryattachment?attachment?uuid={UUID}”.

Indicative example would be: “https://ics2domain/ics2-cr-web-ccn2/#/screen/ensdata/binaryattachment?uuid=HRCM-e35003266956-4091-82d9-0f5a7c7fa9b0”.

When the user visits this URI in the CR UI and has the access rights, they will automatically download the attachment.

### **2.2.12 Which roles does the user need to have in order to download the attachment from CR UI?**

Related to the Security Protection, the logged in user allowed to download the attachment are, according to Security Plan:

- Member State – Customer Risk Analyst;
- Member State – Customs Risk Management Official;
- Member State – Customs Control and Clearance Officer;
- Member State – Customs Control and Clearance Manager;
- Member State – Business Process Analyst.

More specifically, every user with any of the above roles is able to download the attachment in case the respective NES of the national user has received this URI.

### **2.2.13 In ICS2 Release 2 a new 'URI' field has been added. The filename field is still mandatory. For an attachment this would be the file name, for a URI, would this be the file path?**

The filename field will remain the same in both cases, as it is populated from the incoming message that contains the attachment.

As the CR application is currently implemented, it expects in the incoming messages (e.g. IExxx) to include inside the Binary attachment at least the FileName, the BinaryObject and the MIME type.

In case the incoming message contains a URI, this will be ignored, since only the CR application generates the URI for the outgoing message (e.g. IE4Q02).



## 2.3 FAQ RELATED TO EO

### 2.3.1 What does mean the condition Cxxx for the optionality of data element 'Commodity code' in an IE3F32 message?

In the data element 'Commodity code' of an IE3F32 message no condition is applied as referred Cxxx does not exist in ICS2-CFSS-R&C-v1.12[R08R08]. Considering that cardinality for 'Commodity code' is 0..1, the 'Commodity code' is Optional in ICS2 Release 1.

Nevertheless, in ICS2 Release 2, Cxxx is replaced with C3025 in IE3F43 messages and data element 'Commodity code' is Conditional. With respect to IE3F32 message, Cxxx is removed and data element 'Commodity code' is Optional.

### 2.3.2 What is the process in case an EO would like to add further good items within an existing ENS filling?

It is not possible for new good items to be added to an existing ENS filling. The EO must invalidate the initial ENS filling and to lodge a new one including the new good items.

### 2.3.3 In case an EO (sender) asks for a message with specific LRN, what is the process for detecting such message at central side?

- The EO should raise this request to its respective NSD for further investigation. If needed, the NSD will raise this issue to the CSD;
- ITSM3-TES will search on ICS2 Monitoring & Business Statistics tool. In case the message cannot be detected, TES will extend the search to Kibana;
- In case no message detected, ITSM3-TES will address the LRN to ITSM3-OPS TAPAS Team in order to check at TAPAS level;
- If no message has been identified after above actions, the LRN will be addressed to ITSM3-OPS Network Team to search on F5 logs.

### 2.3.4 How the phone numbers which are included in the ENS Filings (sent by the EOs) are validated from STI? Please also include some examples.

In the STI, when the communication type is "TE", it is validated against rule R3006.

The pattern, which the rule is checking is the following one:

ITU\_E123\_PATTERN = "^\\+(?:[0-9] ?){6,14}[0-9]\$"

The pattern `^\\+(?:[0-9] ?){6,14}[0-9]$` can be explained as three parts:

1. A string is required in which the first character must be '+' (pattern part: `\\+`);
2. Then, a digit from 0-9 followed by a space character can be repeated minimum 6 times and maximum 14 times (pattern part: `(?:[0-9] ?){6,14}`).

Note that space character after a digit is not mandatory and can appear only one time.

3. After that, a digit from 0-9 is required (pattern part: `[0-9]`).

Please find below some valid and invalid examples:

+3067493493 valid

+30 67493493 valid

+3 0 5 6 7 8 3 valid

+ 30 67493493 invalid (space character after '+')

+30 6743 invalid (digits after '+' are 5 and not 6, space is counted as one repetition with digit 0)

+30 1234567891011123 invalid (characters after '+' are 17, maximum length exceeded)

General note: Regardless the pattern, a valid international phone has the following format: +XX NNN XXXXXXXX where XX = country code, NNN = city code, XXXXXXXX = number.

Is there any alert which is triggered before the expiration of the registered certificates in the UUM&DS system?

### **2.3.5 Is there any alert which is triggered before the expiration of the registered certificates in the UUM&DS system?**

The user can subscribe to the notifications via ADMIN-EXT, in “Dashboard” section, select “My Notifications” and then select “Expiring user certificate”.

The user should check in due time that the certificate is active, also the user is responsible to renew it before its expiration date. This will ensure that there will be no interruption in operations due to certificate expiration.

### **2.3.6 Will there be the possibility for EOs with few movements to lodge their ENS via a GUI, as it will not be feasible for these EOs to develop a full-fledged ICS2 system-to-system application?**

It will be feasible for the EOs to lodge the ENS using EU Customs Trader Portal ICS2 Shared Trader Portal (STI-STP): EO needs to have EORI number, EO needs to successfully log into EUCTP (STI-STP) via UUM&DS authentication and identification. The EO needs to fill all data required for ICS2 ENS filings as per Common Functional Technical Specification.

Using STI-STP EO can also verify the status of their submission, make amendments to submitted ENSs, configure preferences related to notifications and check notifications.

### **2.3.7 Is there anything an Airline Company has to do in order to announce an ITSP being the technical connection?**

There is no need to register the IT service supplier. The ITSP acts as Sender who is delivering the messages to STI on behalf of its clients.

The relation between the Economic Operator (Airline) and IT Service Provider does not need to be registered in anywhere.

On the other hand, in case of any legal dispute, IT Service Provider needs to prove to Customs Authorities that such relation was established during the period when messages were sent to ICS2.

### **2.3.8 What should be the business content of messages if the user of the services of an ITSP is a GHA (Ground Handling Agent) that represents multiple Airline Companies?**

The business content of messages will have to include both the Airline EORI number and GHA (Ground Handling Agent) EORI number in respective ENS messages attributes, in this case:

- Airline Company - would be declarant;
- Ground Handling Agent – would be representative;
- ITSP would be technical sender only in AS4 message.

## 3 CONFORMANCE TESTING FREQUENTLY ASKED QUESTIONS (FAQ)

### 3.1 FAQ RELATED TO MS

#### 3.1.1 What is the use of Synergia and how to obtain a Synergia account?

For the purposes of CT campaign and later for the operations in production, the official platform to be used is the Synergia ESS. All the service requests, requests for information, notifications and incidents that might occur as well as investigations and resolutions for the issues or the problems, will be registered and handled via this ticketing system.

As per MS – CTOD [R07], in order to obtain a Synergia account, the user shall navigate to ITSM Portal (<https://itsmtaxud.europa.eu/sites/itsm-portal/home.html>) and choose "Not registered yet?" and provide the filled-in and signed by NPTL form to ITSM Service Desk ([support@itsmtaxud.europa.eu](mailto:support@itsmtaxud.europa.eu)).

#### 3.1.2 What is the usage of MON&BS as supportive tool to the EO-Self Conformance Campaign?

MS operators shall access ICS2 Monitoring and Business Statistics tool in CONF environment to consult the registered EO Self-Conformance Test campaigns and to follow up the execution of the related business scenarios. The aim is for MSs to provide meaningful assistance to EO during Self-conformance test campaign. The MS might also help EO to configure its access point or communication paths in case the EO has any temporary issue accessing STI-STP. With the Member State Service Support – Monitoring Operator role a user is involved in the following use cases:

- Management of Trader Preference:
  - Consult the trader preferences;
  - Modify a trader preference;
  - Create a new trader with his/her respective preferences;
  - Manage a trader preference.
- EO Self-Conformance Test Campaign:
  - Consult the EO Self-Conformance Test campaigns (consult the business scenarios of each test campaign and consult the messages of each business scenario<sup>1</sup>);
  - Consult successful EO Self-Conformance Testing;
  - Upload successful EO Self-Conformance Testing;
  - Search EO messages not compliant with a successful Self-Conformance testing.

It is important to highlight that the use of ICS2 MON&BS tool is available only to the MS and EC users. The EO can manage ICS2 related preferences and Self-register a conformance test campaign through the STI-STP. In this case, the execution of the Campaign will be tracked by STI.

#### 3.1.3 Who is involved in the IsAlive (connectivity verification)?

Prior to the start of CT activities, a MS should verify the connectivity of the NES with ICS2. To do so, the MS has to send an isAlive request towards the Risk Analysis Orchestration Business Application Service of the ICS2 Common Repository as defined in section 6.1 of the [R14]. This activity will take place in the ticket that will be registered with the submission of the WSDL files. On the same ticket, the

---

<sup>1</sup> This feature is available only in the CONF environment.

Central Operations Team will send isAlive request from central side towards the NES services to confirm that these are up and running. IsAlive tests must take place at least one (1) week before the CT starting date. ITSM3-TES should highlight this activity during the Coordination call. Only when isAlive tests from both central and NES sides are successful, a MS can proceed with CT execution (functional testing).

## 3.2 FAQ RELATED TO EO

### 3.2.1 Which documents should an EO or ITSP Provider consult for their preparation prior to conformance testing?

Trade association representatives can find the published versions of the EO Self-Conformance Testing related documentation on [CIRCABC](#). All EOs can find the publicly accessible EO self-conformance Testing related documentation on the public [CIRCABC](#) and the EO Self-Conformance Testing related training materials in [Customs & Tax EU Learning Portal \(europa.eu\)](#).

For the smooth preparation prior to CT activities, EOs should read and comprehend all the relevant documentation that has been provided to EOs:

- ICS2 Harmonised Trader Interface Specifications[R06];
- ICS2 EOs Common Technical System Specifications package for ICS2 Release 2 [R16**Error! Reference source not found.**].

Particularly, the consultation of the below documents is considered essential during the CT execution:

- Conformance Test Organisation Document (CTOD) for EO for Release 2 [R17];
- Test Design Specifications for EO Conformance Test Cases for Release 2 [R18**Error! Reference source not found.**];
- Test Design Specifications for EO Conformance Test Scenarios for Release 2 [R18];
- Trainings that will be provided by National Administrations to EOs:
  - ICS2 Conformance Test;
  - Digital certificates and registration of certificates;
  - NA services and support to EOs.
- Material which will be made publicly available in [Europa](#) webpage:
  - Self-Conformance Test (EO-CT);
  - UUM&DS system: Your passport to EO applications (EO-UUM&DS);
  - Business Continuity Plan (EO-BCP);
  - Use of STP for ENS registration (EO-STP).

In general, the latest accepted version of the EO Self-Conformance Testing related documentation is stored on:

[https://circabc.europa.eu/ui/group/ea5f882b-9153-4fc1-9394-54ac8fe9149a/library/3a95f619-b6f0-4286-9673-466190f8fb88?p=1&n=10&sort=modified\\_DESC](https://circabc.europa.eu/ui/group/ea5f882b-9153-4fc1-9394-54ac8fe9149a/library/3a95f619-b6f0-4286-9673-466190f8fb88?p=1&n=10&sort=modified_DESC).

### 3.2.2 Which is the URL for ICS2 STI-STP User Interface?

An EO can access STI-STP through the following link: <https://conformance.customs.ec.europa.eu/gtp>

### 3.2.3 Which steps should be followed by an Economic Operator (or an ITSP) in order to establish the AS4 connectivity prior to the conformance testing?

- Deploy one or more Access Point(s) according to HTI Interface Control Document specifications [R06];

- Obtain a TLS certificate to be used at the transport layer (https) for identifying itself following the 2-way TLS security mechanisms;
- Obtain a sealing certificate to be used for sealing at message layer (see section 4.6.2 of the HTI Interface Control Document [R06]);
- Sender must be registered by Customs Authorities following the agreed national procedure. This includes the upload of the sealing certificate;
- Configure their own AS4 Access Point(s) in STI-STP:
  - Log in on EUCTP and access STI-STP via UUM&DS authentication and identification;
  - Select "Manage Preferences"<sup>2</sup> from STI-STP menu;
  - Add information on "Party Id definition":
    - Provide the Party ID (The Party ID format is defined in section 4.2.2.1 of the HTI Interface Control Document [R06]);
    - Define Message Exchange Pattern ("push" or "pull");
    - Provide the Endpoint (i.e., URL) (Available if the MEP is "push");
    - Provide the Certificate Authority that issues the TLS certificate;
    - Insert Technical details (Name, Email address, Phone).
  - Add information on "Default communication path":
    - Select Business domain (Postal, Maritime, Air, Rail, Road, Express);
    - Select Communication path (UI, S2S);
    - Party Id ID (Mandatory in case the communication path is S2S).

### 3.2.4 How many certificates should be used by the EOs?

Each EO should obtain:

- A TLS (Transport Layer Security) certificate from a trusted Certificate Authority to be used at the transport layer (https) for identifying itself following the 2-way TLS security mechanisms. A Trusted CA in the TLS context can be a commercial CA trusted by DG TAXUD. The CA used need to be notified to DG TAXUD, but the certificate does not require registration;
- A digital certificate to be used for sealing at message layer, which should be registered in the National UUM&DS Application or in the Central UUM&DS Application (see section 0). In case that an EO uses the services of an ITSP, then this EO does not need to register this certificate since it will be done by its ITSP.

### 3.2.5 From which Certificate Authorities (CAs) an EO can issue its certificate for ICS2 message sealing (signing)?

The digital certificate for message sealing must be issued by a Certificate Authority (CA) that is on the official EU wide LOTL<sup>3</sup> or on the National Customs alternate list of the Member State to whom National UUM&DS would like to register this certificate.

The Certificate Authorities (CAs) on the LOTL can be divided into two categories:

1. CAs that issue qualified certificates;
2. CAs on the LOTL that issue non-qualified certificate for e-signature/sealing.

CAs for both categories are published in <https://esignature.ec.europa.eu/efda/tl-browser/#/screen/home>.

A certificate issued by the CAs on the LOTL can be used to perform registration at a National Customs Authority of any EU Customs authority. Alternatively, an EO can use a certificate issued by other CAs

---

<sup>2</sup> User manual is provided as part of the STP application and supported by training material (to be delivered).

as long as the CA is present on the “National Customs Alternate List”<sup>4</sup>. Certificates issued by such CA can only be used to perform the registration at National Customs Authority.

### **3.2.6 Who is responsible for managing the National UUM&DS alternate list?**

A MS is responsible for managing the National Customs alternate list.

### **3.2.7 Who is responsible for managing the LOTL?**

The actual content of LOTL is managed and published by each MS.

### **3.2.8 How does an EO communicate its sealing certificate?**

Each EO should register its sealing certificate in the National UUM&DS Application of its Member State. In case there is no National UUM&DS application, the Member State should decide if Central UUM&DS application should be used. The process for the latter case is described in the UUM&DS Central Certificate Registration Manual for EOs, which is published in PICS:

<https://webgate.ec.europa.eu/pics/filedepot/24416?fid=62623>

### **3.2.9 How to verify the successful registration of EO System digital certificate?**

Considering that the registration of each EO System certificate is done in the corresponding National UUM&DS application, where neither DG TAXUD nor the contractors provide any access, the successful certificate registration may only be verified by the EO itself.

Nevertheless, the successful certificate registration is a precondition for the execution of all EO functional test cases. This means that, in case that the certificate was not correctly registered, TAPAS will return the EBMS:0004 exception with subcode: A001 to the EO and will not allow any further EO message exchange.

### **3.2.10 Can an EO register the same sealing certificate in CONF and PROD?**

An EO can use the same sealing certificate that has been used for CONF as long as it is registered in UUM&DS, but it has to be registered also in UUM&DS in PROD.

### **3.2.11 What is usage of sealing certificate in AS4 message exchanges with ICS2?**

The EO has to configure AS4 access point to sign (seal) the AS4 messages with the given certificate and should embed the full certificate path inside the AS4 message. This is established by configuring set-up to embed a wsse:BinarySecurityToken with a valueType attribute of type X509PKIPathv1 as per section 4.6.2 of ICS2 HTI – ICD [R06]. A certificate path is the chain of certificates from the Root Certificate of the CA - intermediate certificate issued by the CA/n - EO leaf certificate as issued by the CA. This is a critical aspect.

### **3.2.12 How to register a sealing certificate depending if you are or not the holder of the key?**

Certificate registration can be performed in one of the following ways:

### 1. Holder of the Key:

- a. Log in as an EO (in the WAYF) and access Admin-Ext (in case of Central Certificate Management) or the relevant MS site (in case of Local Certificate Management);
- b. EO registers the certificate using the certificate's private key.

### 2. Not Holder of the Key: (process valid ONLY for Central Certificate Management)

- a. EO creates a delegation to one of the employee;
- b. EO shares public key with the employee;
- c. Employee registers his own certificate (as Holder of the Key);
- d. Employee logs in using the delegation from the EO;
- e. Employee registers the EO's certificate (using the public key) and signs the registration with his own private key (from the certificate he has already registered).

## 3.2.13 How to use UUM&DS system?

The following URL redirects to an online course that provides EO with specific information about how to use the UUM&DS. Upon completion of the course, an EO will be able to confidently work with the UUM&DS and carry out delegation, certificate registration and authentication processes within the UUM&DS process flow.

Attend course by accessing the following URL:

<https://customs-taxation.learning.europa.eu/course/view.php?id=494&section=1>

## 3.2.14 Which UUM&DS Business Profiles should an EO have in the scope of Self-Conformance Test Campaign?

In the scope of Conformance Testing Campaign, an EO or a Customs Representative should have 'STISTP\_EXECUTIVE' and/or 'STISTP\_CONFIGURATOR' business profiles to grant the access rights of the required STI-STP roles.

UUM&DS Business Roles vs Corresponding STI-STP roles			
UUMDS type of actor	Delegated from	UUMDS business profile configured as available	STI-STP role
Economic Operator (Trader and ITSP)		EXECUTIVE	EO-DECL
		CONFIGURATOR	EO-CONF
		EXECUTIVE_LIMITED	EO-PNA
		CONSULTATIVE	EO-NOP
Employee*	Economic operator	EXECUTIVE	EO-DECL
		CONFIGURATOR	EO-CONF
		EXECUTIVE_LIMITED	EO-PNA
		CONSULTATIVE	EO-NOP
Customs Representative		EXECUTIVE	EO-REP
		CONFIGURATOR	EO-CONF
Employee*	Customs Representative	EXECUTIVE	EO-REP
		CONFIGURATOR	EO-CONF



### 3.2.15 Which EORI number should an EO use?

- In case that an EO implements its own access point, then the EO holds both Sender and Declarant roles and should use its unique EORI number, in order to register its certificate and also use it in the functional payload (ENS filing);
- In case that an EO uses ITSP services, then the IT Service Provider holds the Sender role and should register a certificate with its own EORI number. However, the EO still holds the Declarant role and should use its own EORI number for the ENS filing.

### 3.2.16 How should an EO configure P-Mode?

An EO should follow Annex II P-MODES SUMMARY from ICS2 HTI – ICD [R06] also published on PICS:

<https://webgate.ec.europa.eu/pics/filedepot/20607?cid=19248&fid=79935>

Specifically, Annex II includes all the required P-Mode configuration parameters. In addition, an EO should consult section 4.6.3 of the same documentation, which describes a particular configuration on the handling of the TLS certificates that cannot be expressed as a P-Mode parameter but is nevertheless an AS4 configuration element.

### 3.2.17 In the response messages an EO receives from TAPAS, what is a globally unique identifier for a specific multipart/related MIME part?

Such unique identifier is the eb:MessageId + the Content-Id of the part (In AS4 terms: eb:MessageId element value + eb:PartInfo@href attribute value of the given part).

### 3.2.18 What should be the "MPC" use attribute in an incoming user message?

According to ICS2 HTI – ICD [R06] section 4.1.3.3, for an incoming user message the @mpc attribute should not be specified, thus, this results in the usage of the default MPC.

### 3.2.19 Which are the most common issues identified during the ICS2 connectivity setup trials with EOs/ITSPs?

- In the messages sent to TAPAS, most EOs/ITSPs erroneously include the leaf certificate instead of the full certificate chain, (please check section 4.6.2 from the ICS2 HTI – ICD [R06]);
- The receipt messages sent from an EO to TAPAS, it is observed to be wrongly signed (the empty SOAP body is not part of the signature). The receipt message occurs when an EO receives a user message from TAPAS. Then, the EO responds back with a receipt message indicating that it has successfully received the user message from TAPAS. The SOAP Body of this receipt message should be signed, otherwise TAPAS fails to validate the receipt messages received back and finally considers that the initial user message was never sent to EO.

### 3.2.20 Which elements should contain unique values in the ENS fillings?

The Technical Message header ID number should be unique per declarant for each message sent by an EO. The LRN number should be unique too, otherwise the message will be rejected with an IE3N99. There is a requirement for Transport document (master level) to be unique for at least 1 year. For Transport document (house level) it is advised to be unique but it is not mandatory. Within the same house level ENS filing there should not be repetitive Transport document (house level) number. In F32 messages combination of Transport document (house level) and Reference number/UCR should be unique for at least one year.



### **3.2.21 What is the meaning of the N99 error codes?**

As the ICS2 interactions with traders are asynchronous, validation of an incoming message can result in functional errors being detected after the reception. In that case, a functional error message is asynchronously sent to the sender. This message is defined as IE3N99 for a general validation error.

### **3.2.22 Which is the correct expression for the time values inside fillings?**

For all elements that contain timestamps, the values should be expressed in UTC format. This expression is the GMT zone followed by letter “z”. No local time zones or central European time should be used in that expression. An alternative way could be to use the local time followed by an offset (which points out the difference of that local time from the GMT). For more information, please refer to section of 4.2.1 of ICS2 HTI – ICD [R06].

### **3.2.23 How should an EO raise an issue to Service Desk?**

Structural issues with the system of the EO should be addressed to the National Service Desk where the EO has registered its EORI number.

The issues that are related with the certificates of an EO should be addressed in the National Service Desk where the certificates were registered. This will be in the majority of cases, the National Administration where the EORI number was registered but can differ from that sometimes, in particular when an ITSP for operating an ICS2 access point is used for the submission of messages by the EO.

The National Service Desk is responsible for resolving any issue/incident that occurred or dispatch them to Central Service Desk. The responsible National Administration will share the information of the relevant tickets (that are registered in SYNERGIA ESS) with the EO.